## Storm - HYDRO 2





Hydro 2 is built for durability and strength and is ideal for indoor or outdoor promotions. The moulded base can be filled with either water or sand, making it especially suitable for high traffic areas indoors or poor weather conditions outdoors.

## features & benefits


- Suitable for indoor or outdoor use
- Can be used as a double or single sided unit
- Ideal for point of sale, retail display or exhibitions
- Moulded plastic base for water or sand weighting
- Supported on a simple eyelet system
- Weather resistant
- Supplied with carry bag
- Designed to withstand approximate wind speeds of 10-12 miles per hour (Beaufort scale 3)



hardware specifications	graphic specifications	additional info
Assembled dimensions (mm): 2135 (h) x 813 (w) x 533 (d) approx	Please refer to graphic template	Included in kit: Base, support arms, graphic fixing and carry bag.
Base footprint dimensions (mm): 533 x 394 approx		Availability: Dark grey base, mid grey support arms
Weight: 7.7kg approx when empty 20.6kg approx when filled with water		Recommended accessories: AB120A 850 x 150mm dia banner tube (to transport graphics safely)

We are continually improving and modifying our product range and reserve the right to vary the specifications without prior notice. All dimensions and weights quoted are approximate and we accept no responsibility for variance. E&OE.

## **Assembly Instructions**



Kit includes: Base, support arms and carry bag.



Assemble the top section of the poles into the locators in the middle section of the graphic support



To attach the graphic align the hooks found on the graphic support with the eyelets on the graphic and attach each one.



insert the graphic fixing into place by pushing the fixing into the channel on the base



Assemble the remaining bungee support poles.



Remove cap and fill the base with water or sand.



Slot the poles into the locator on the base furthest away from the graphic fixing



Once all the bungee poles are fully assembled the graphic can be attached

